


(10) 0.656 (16.7)∅
Mounting Holes Based on 12
equally spaced as shown
on 28.750 (730.3) bolt circle



(14) 1.062 (27.0)∅
Mounting Holes Based on 16
equally spaced as shown on
42.000 (1066.8) bolt circle

Patent Pending

Size	Number of Water Cooled Disc	Number of Air Cooled Disc	Pressure Applied Torque @ 80 psi (lb in)	Spring Applied Dynamic Torque (lb in)	Spring Applied Static Torque (lb in)	Thermal Rating (HP)	D (inch)	D ₂ (inch)	J (inch)
224WCSB	1	1	100,000	256,000	252,000	270	18.70	12.88	31.00
324WCSB	2	1	200,000	337,000	304,000	540	22.74	16.82	31.00
324WCSB	1	2	100,000	396,000	413,000	270	21.68	16.82	31.00
424WCSB	4	0	400,000	307,000	214,900	1,080	27.84	20.47	31.00
424WCSB	3	1	300,000	422,000	361,000	810	26.78	20.47	31.00
424WCSB	2	2	200,000	476,000	465,000	540	25.72	20.47	31.00
424WCSB	1	3	100,000	530,000	569,000	270	24.66	20.47	31.00
236WCSB	1	1	295,000	1,112,000	1,116,000	650	26.50	15.50	45.00
336WCSB	2	1	590,000	1,430,000	1,325,000	1,300	31.50	20.00	45.00
336WCSB	1	2	295,000	1,796,000	1,906,000	650	30.10	20.00	45.00
436WCSB	4	0	1,180,000	1,404,000	983,000	2,600	38.00	24.88	45.00
436WCSB	3	1	885,000	1,740,000	1,528,000	1,950	36.56	24.88	45.00
436WCSB	2	2	590,000	2,077,000	2,072,000	1,300	35.00	24.88	45.00
436WCSB	1	3	295,000	2,413,000	2,617,000	650	33.63	24.88	45.00